

Wall2Floor Rasal NF

Cement Putty for Wall2Floor NF System.

DESCRIPTION

Wall2Floor Rasal NF is a cement putty made of highly selected natural sand, binding agents and special additives for a perfect adherence with the substrate and a perfect workability.

USES

Smoothing product for horizontal and vertical surfaces. Please refer to the **"Wall2Floor NF System"** TDS.

IDENTIFICATION FEATURES

Nature of Binder: white cement and acrylic resins. Aspect: powder.

TECHNICAL PERFORMANCES

Wall2Floor Rasal NF permits to obtain an even and uniform surface.

SUBSTRATE PREPARATION

Please refer to the "Wall2Floor NF System" TDS.

APPLICATION

Please refer to the "Wall2Floor NF System" TDS.

DILUTION

Dilute each bag of 25 kg with 5-6 lt of clean water. Mix the paste gently with a drill fitted with a whisk for 3 minutes.

Product pot life: 60 minutes approx. at 25° C, UR=60%.

RECOMMENDATION

The material must be protected from cold and high heat during the entire application cycle.

Do not apply with air, support and product temperature lower than $+5^{\circ}$ C or higher than $+35^{\circ}$ C, nor under direct sun light, nor over extremely hot surfaces (even if already in the shadow). Environmental humidity must be <75%; substrate humidity must be <10%.

It is advisable to complete each project with material from the same batch of production.

For the correct use, dilution and application of the products here mentioned, consult their respective technical data sheets.

During the preparation of the substrate and application of the products, it is recommended the correct use of tools and individual protective devices (dpi).

TOOLS CLEANING

With water, immediately after use.

YIELD

Wall2Floor Rasal NF (powder): 1,5–2,5 kg/m², in two coats, depending on the type of intervention and substrate conditions.

COLORS

White.

PACKAGES

25 Kg bags.

SHELF LIFE

The packaged product is guaranteed for 24 months, if stored in the original sealed package and at temperatures between +5°C and +35°C.

Contains: cement

Irritant / risk of serious eye damage / irritation of the skin / Keep out of the reach of children / If swallowed, seek medical advice immediately and show this container or label.

The product must be transported, stored and used in accordance with current standards of hygiene and safety, let dry completely and treat them as special waste. For more information see the safety data sheet

NB- NOVACOLOR ensures that the information herein has been provided to the best of its experience and its technical and scientific knowledge, but cannot take any responsibility for the results obtained by using them as the conditions of application are beyond its control. We recommend to check the suitability of the product to each specific instance. This TDS cancels and replaces all previous editions.

TDS: Wall2Floor Rasal NF Revision n: 02 Date: 09-05-2016 Page 1 / 1