

Wall2Floor Top Coat Fine

Mineral coating for interior and exterior horizontal and vertical surfaces.

DESCRIPTION OF THE PRODUCT

Wall2Floor Top Coat Fine is a mineral coating for the decoration of interior and exterior horizontal and vertical surfaces.

APPLICATIONS

Top quality indoor decoration, in line with the most modern and current trends in "concrete" in the field of architecture.

IDENTIFICATION FEATURES

Paste product.

PERFORMANCE CHARACTERISTICS

A continuous, seamless surface can be obtained, thanks to its particular formulation.

PREPARATION OF THE SUBSTRATE

Refer to the "**Wall2Floor System**" technical sheet.

APPLICATION

Refer to the "**Wall2Floor System**" technical sheet.

PREPARING THE MIXTURE

Before application, add a 5 kg packet of **Wall2Floor Component B** to every 15 kg packet of **Wall2Floor Top Coat Fine**, with the aid of a mechanical mixer fitted with a whisk.

Mix the compound for approx. 3 minutes. The mixture obtained must not have lumps, portions of unmixed components, impurities.

Dilution: when the two components have been mixed completely, up to 5% of water can be added.

Lifespan of the mixture: approx. 90 minutes.

PRECAUTIONS

Do not expose the products to direct heat sources or temperatures below +5°C for long periods of time.

If the products are stocked at temperature of approx. +5°C, before use it is recommended to take them to a place with suitable temperature, in a way to condition them to a temperature of use no lower than +10°C. Do not heat the products using a direct heat source, flame, hot body or similar.

It is recommended to finish the job using the same production batch. If different batches are used, we advise mixing the different batches together in order to avoid slight colour differences.

The application of the "**Wall2Floor System**" outdoors, means light colours must be selected and outdoor-resistant colorants must be used.

After application, the surfaces must be protected from rain and humidity until they are completely dry.

Exposure of the surface, which is not completely dry, to atmospheric agents, can generate the appearance of stains or irreversible bleaching phenomenon.

For correct use of the materials mentioned, dilution and application, read the relative technical data sheet carefully.

Correct use of individual protection equipment (PPE) is recommended during all preparation of the substrate, products and application of the same.

CLEANING EQUIPMENT

Clean with water immediately after use.

COVERAGE

Wall2Floor Top Coat Fine: 1.0-1.2 kg/m², in the two layers, on the basis of the type of intervention and the status of the substrate. It is good practice to check the effective coverage via a preliminary test on the specific substrate.

COLOURS

White and colours of the **Wall2Floor** chart.

PACKAGING

15 Kg packets.

STORAGE CONDITIONS AND SHELF LIFE

In its original packaging and correctly sealed, and as long as it is kept in a covered warehouse at a temperature between +10° C and +30° C, the material has duration of 24 months.

SAFETY INDICATIONS

Directive 2004/42/EC:

Wall2Floor Top Coat Fine (paints for a decorative effect):

EU limit value for Wall2Floor Top Coat Fine (cat A/I): 200 g/l (2010)

Wall2Floor Top Coat Fine contains maximum 200 g/l VOC

The product is not subject to labelling pursuant to the regulations in force.

Use the product in compliance with the hygiene and safety regulations in force. Do not throw residues into the drain system, into waterways and onto the ground. After use do not disperse containers in the environment, leave the residues to dry well and handle them as special waste. Keep out of the reach of children. In the case of ingestion, seek medical help immediately.

For further information, refer to the MSDS.

N.B. - COLORIFICIO NOVACOLOR guarantees that the information herein is provided to the best of its experience and its technical and scientific knowledge; however, it cannot assume any liability for the results obtained using these products since the conditions of application are beyond its control. We recommend that you always check the suitability of the product to each specific use. This current edition supersedes all previous information sheets.